

PP 809 High Performance Fanfold Matrix Printer



PP 809 with options printer stand and PM SER/PAR

- Heavy duty 24-wire dot matrix printer
- Flatbed technology using print bar
- High Performance:
 - 1000 cps (10 cpi)
 - 800 pages/hour
 - 500 lines/minute (60 cpl)
 - 40,000 pages/month
- Dual paper input: 2 tractor cassettes and manual paper feed
- Lowest cost per page through 30 Mio character ribbon
- Wide print format up to 17.7 inches (165 col.)
- Easy user operation via macro functions
- Precise print registration
- Personality Modules (interfaces) for major host and network environments

The PP 809 combines the performance of a line printer with the flexibility of a dot matrix printer. The rugged design and the Intellidrive™ Technology guarantee reliable unattended printing and a workload of up to 40,000 pages per month. Two accessible tractor cassette gives a high flexibility for the print production. The precise print registration allows to print also on multi-part form sets with high speed and accuracy. The PP 809 is a cost-effective alternative to line printers.

TECHNICAL DATA

Printer Specification

Technology:	serial impact dot matrix
Printhead:	24 wires, 0.25 mm needle diameter; life time 400 million characters
Print mode:	high speed draft (HSD), data (DQ), near letter (NLQ) and letter quality (LQ)
Print format:	165 characters at 10 cpi
Ribbon:	cartridge nylon ribbon black, 30 million characters, auto ribbon run control
Dimensions:	734 x 280 x 295 mm (WxDxH) (28.9 x 11.0 x 11.3 inch)
Weight:	approx. 20 kg (43.5 lb)
Diagnostics:	selftest, hexdump, remote diagnostics via interface
Operator Panel:	16 digit LCD display, trilingual (German, English, French)
Keyboard:	Membrane tactile type with Ready/Stop LED
Rated voltage:	100 - 125 VAC / 200 - 240 VAC 3A / 1.5A / 50 - 60 Hz
Power input:	operating approx. 200 W, 40 W Standby
Environmental temperature:	operating: +10 to +35 °C (+50 to + 95°F) 20 to 80% rel. humidity storage: -40 to +70 °C (-40 to +158°F) 5 to 85% rel. humidity
Noise level:	approx. 55 dB(A) acc. to ISO 7779
Agency approvals:	VDE/GS, UL, CE, FCC-B

Performance

Print speed: (10 cpi)	HSD: 1,000 cps	DQ: 750 cps
	NLQ: 430 cps	LQ: 216 cps
Throughput: (ECMA 132, fanfold, 1-ply)	HSD: 800 pages/hour	
	DQ: 760 pages/hour	
	NLQ: 580 pages/hour	
	LQ: 370 pages/hour	
Duty cycle:	40,000 pages per month	
MTBF:	15,000 hours at 30% duty cycle	

Paper Handling

Paper path:	flatbed design; 2 paper inputs, 1 output for fanfold paper, paper path selectable via software or operator panel
Paper input:	two removable tractor cassettes
Paper output:	to the rear with zero tear Off
Paper weight:	60 to 100 g/m ² formsets up to 350 g/m ²
Paper Thickness:	printing: max. 0.7 mm (0.028 inch), transportation: max. 2.0 mm (0.08 inch)
Paper width:	102 to 450 mm (4 to 17.7 inch)
Form feed:	20 inch/second;
Automatic Gap Control (AGC):	optimizes automatically the print gap according to paper thickness
Copies:	1 original + 3 copies

Connectivity

	PERSONALITY MODULE SER/PAR
Interfaces:	parallel Centronics and serial RS-232C/RS422, shared mode
Emulations:	IBM Proprinter XL24 (AGM), Epson LQ 2550/1060/ESC/P2
Buffer:	up to 64 KByte
Character sets:	ISO 8859/1, ISO 8859/15; IBM Set 1/Set 2 in 14 national versions; IBM Code Pages 437, 850, 858, 860, 863, 865; Epson Ext. Char. Set in 15 national versions; Eastern European character sets optional
Fonts:	draft quality: High Speed Draft, Data and Data Large; Near letter and letter quality: Courier, Sans Serif, OCR-A, OCR-B, Orator, Orator-C, Prestige, Roman, and Script
Character attributes:	bold, italic, shadow, outline, double strike, underline, double underline, overline, strike through, sub/ superscript, double to octuple, for Data Large 99-fold size
Pitches:	10, 12, 15, 17.1, 18 and 20 cpi, proportional
Line spacing:	2, 3, 4, 6, 8, ... 360 lpi
Barcode:	EAN 8, EAN 13, UPC-A, UPC-E, Postnet, KIX Code, Code 39, Code 93, Code 128 (incl. EAN 128), Codabar, 2 of 5 industrial, 2 of 5 interleaved, and MSI Mod 10/10
Graphics:	360 x 360 dpi max.
Macros:	parameter settings for up to four individual printer configurations, selectable via software or operator panel

OTHER PERSONALITY MODULES

Ethernet:	Ethernet 10BaseT/100BaseTX RJE45
Ethernet IPDS:	Ethernet IPDS Emulation
Twinax IPDS:	IBM Twinax and IPDS Emulation
SER/PAR HP:	SER/PAR PM with HP2934/2235 Emulation
Ethernet HP:	Ethernet PM with HP2934/2235 Emulation
WLAN:	Wireless LAN PM according to IEEE 802.11b for Europe, Emulations like PM SER/PAR
SER/PAR MT 50:	Tally MT 50 Emulation
SER/PAR Genicom:	Genicom Emulation
Code V IAS 2:	
Ethernet IGP:	Printronix IGP/10/20/40 Emulation
Parallel IGP:	Printronix IGP/10/20/40 Emulation

Printer drivers for Windows 3.x/95/98/2000/NT 4.0 are available.
SAP R/3 device types are available for download.

Options

Printer stand:	for handling of dual fanfold paper input, dimensions: 635 x 660 x 840 mm (WxDxH) (25.4 x 26.4 x 33.6 inch); weight: approx. 20 kg (43.5 lb)
Tractor cassettes:	additional tractor cassettes can be loaded with paper to be ready for quick plug-in once required. Very helpful if several different types of media are used alternatively.
Interface:	Personality Modules

This is only an extract of the product specification. For a detailed specification it is referred to the comprehensive product documentation.
Specifications are subject to change without notice. All registered trademarks are the property of their respective companies.

PSi Printer Systems international GmbH

Eiserfelder Strasse 316
57080 Siegen, Germany
Tel: +49 271 3597 - 101
Fax: +49 271 3597 - 190

e-mail sales@psi-si.de
Internet www.psi-si.de

